

PG Multiplexer

interface multiplier
for the S5 PG

Two devices on one PG interface at the same time.
Compatible with all S5 PLCs.

AREA OF APPLICATION

- Simultaneous operation of programming device, text display, operator panel or other process devices

PG-MUX II |||

for two PGs, including connection cable (see below)



PG-MUX II

PLC interface:	TTY (20 mA), active
PG1 + PG2 interface:	TTY (20 mA), active
Protocols:	2 x AS511 or 1 x SINEC® ¹⁾ -L1-BUS and 1 x AS511
Power supply:	230 V AC and 24 V DC
Dimensions [in mm]:	L= 190, D= 110, H= 50
Order number:	400-9361-05

MINI-MUX |||

for one PG and one OP, exclusive of connection cable



MINI-MUX

PLC interface:	TTY (20 mA), active
PG interface:	TTY (20 mA), active
Protocols:	AS511
OP interface:	TTY passive
Protocols:	AS511 or SINEC® ¹⁾ -L1-BUS
Power supply:	24 V DC
Dimensions [in mm]:	L= 135, D= 110, H= 50
Order number:	400-9361-01

Accessories: Connection cable Multiplexer – PLC TTY |||



3 m, TTY, 15pin D-sub male – TTY, 15pin D-sub female
(included in the range of delivery of PG-MUX)



Connection cable Multiplexer – PLC TTY

Order number:	400-9361-03
---------------	-------------

1) SINEC® is a registered trademark of the Siemens AG.